

PFAFF

fine sewing

422 1422

Two-needle, lockstitch special high-speed seamer
with compound feed



Single or two-needle seams on light to medium fabrics e.g. shirts, blouses, jeans and leisurewear etc.

422

For sewing delicate materials e.g. microfiber and silk with the A-version.

1422

Large vertical sewing hooks.
Large bobbin volume.

1422 with subclass -720/04

For setting pockets onto sportswear, leisurewear and work clothing.

- Perfect corner stitching due to left or right disengageable needles.
- Single- and two needle operation at full speed.
- Needles can be engaged and disengaged even at maximum speed.
- Precise positioning of the starting stitches with the "stitch placement" key.

Accessories

- Thread trimmer -900/81
- Backtacking facility -911/35
- Presser foot lifter -910/04
- Pneumatic thread trapper -906/09 (optional).
 - No knotting of loose threads.
 - Starting threads are not pulled out of the needle.



Specifications

- Needle gauge: 3.2-12.0 mm, depending on accessories installed

422

- Versions: A and B
- Max. speed in s.p.m.: 5000
- Max. stitch length: 4.5 mm
- Sewable thread: up to 40/3 synth.

1422

- Versions B and C
- Max. speed in s.p.m.: 4000
- Max. stitch length: 6 mm
- Sewable thread: up to 30/3

Hotlines:

Technical service : ++49-175/2243-101

Application consultancy : ++49-175/2243-102

Spare-parts hotline : ++49-175/2243-103



PFAFF Industrie Maschinen AG

- Postfach 3020
D-67653 Kaiserslautern
- Königstr. 154
D-67655 Kaiserslautern

Telefon: ++49-631/200-0

Telefax: ++49-631/17202

Internet: www.pfaff-industrial.com